



Intermec

## Product Profile

- **Designed to Last**  
Tough, rugged full metal casing is ideal for today's dynamic warehouse, distribution and manufacturing environments.
- **Economical and Reliable**  
Economical price along with high reliability makes the 3400 a printer of choice for applications requiring distributed printing.
- **Flexible**  
A variety of operating modes such as tear-off, label auto-peel, and cutter attachment, ensure long-term flexibility.
- **World-wide Languages**  
The 3400 provides expanded on-board global language support and standard support of most 2D bar code symbologies.



### EasyCoder™ 3400 PRINTER

Our best selling printer just got better. Meet your requirements for a value-priced, versatile printer with Intermec's most popular printer. The EasyCoder 3400 with its 11.43 cm (4.5") maximum label width, unlimited label length and 203 dpi resolution makes it suitable for most of today's bar code label standards. It's also reliable enough for all but the very highest production environments. Featuring metal construction, the 3400 is built for the toughest environments.

Current 3400 series users will see many enhancements over earlier 3400 series printers. The 3400 now comes with Intermec's new powerful IPL3™ printer language with GLOBE™ worldwide language support. GLOBE™ allows the printer to automatically adjust to character mapping standard, including those for Asian double-byte fonts. In addition, the UNICODE standard language

and other well known character mapping standards such as ASCII, Shift-JIS, Big 5, GB and IBM Codepage are all intelligently self-managed and do not require an external font card. Popular 2D symbologies have also been added as standard features.

Overall performance of the 3400 has been enhanced. Print speed has been increased from 5"/second to 6"/second and RS-232 serial port communication speed has been doubled. A heavy duty cutter with tray option is available on the 3400D. Of course, the 3400 is fully backward compatible with 3400A/B/C printers and is backed with Intermec's 12 month warranty.

It all adds up to a powerful printer that is designed and built to be the right solution for the majority of industrial bar code applications.

Intermec

**General**

General Purpose Industrial Direct Thermal/Thermal Transfer Printer. Prints high quality bar codes on pressure sensitive labels and tags in straight through mode.

**Model**

EasyCoder 3400

**Physical Characteristics**

**Length:** 43.8 cm (17.25")

**Width:** 24.9 cm (9.8")

**Height:** 27.7 cm (10.9")

**Weight:** 15.8 kg (35 lbs.)

**Print Specifications**

**Element:** 0.125 mm (0.00492")

**Resolution:** 8 dots/mm (203 dpi)

**"X" Dimension:** 0.13 to 1.27 mm (5 to 50 mil)

**Max. Length:** Unlimited

**Max. Width:** 104 mm (4.1")

**Speed:** 51, 77, 102, or 128 mm/sec (Select 2", 3", 4", 5" or 6")

**Media Specifications**

**Roll:** 152 m (6000" linear)

**Width:** 19 to 114 mm (.75 to 4.50")

**Length:** 13 to 610 mm (0.5 to 24"); fanfold 432 mm (17") max.

**Roll Dimensions:** 213 mm (8.38")

**Thickness:** .08 to .31 mm (0.003 to 0.012")

**Core Size:** 76 mm (3")

**Ribbon Specifications**

**Roll:** 152 m (6000" linear)

**Widths:** 51, 77, 104 mm (2", 3", 4.1")

**Communications**

**Rate:** 1,200 to 38.4K bps

**Asynchronous:** RS-232C, RS-422, RS-485

**Flow Control:** XON/XOFF, READY/BUSY

**Fonts and Graphics**

- 21 resident bitmapped fonts (includes OCR-A and OCR-B)
- 3 resident outline fonts
- Supports user-defined fonts and graphics

**Language**

- IPL3 is an advanced printer programming language that includes many features not available in other bar code printers
- Advanced bar code algorithms handle all required encodation
- Error detection protocols verify secure data transmission
- Command errors and printer status are easily identified to your host.
- Communicates in printable ASCII or control characters
- Globe<sup>TM</sup> support
- Backward compatibility with 86XX and IPL2

**Connectivity**

- Serial interface standard
- Centronics Parallel interface optional
- Internal Ethernet interface optional
- Internal IBM Twinax or Coax interface optional

**Microsoft® Windows**

- Intermec InterDriver<sup>TM</sup> standard Windows 3.x, 9x, NT 4.0/5.0
- Intermec ActiveX<sup>®</sup> controls standard Windows 9x, NT 4.0/5.0
- PrintSet<sup>TM</sup> printer configuration utility Windows 3.x, 9x, NT4.0/5.0
- NetPilot<sup>TM</sup> + Thin Wizard<sup>TM</sup> network configuration utility (with optional Ethernet) Windows 9x, Windows NT 4.0/5.0

**Character Sets**

- Bitmapped using printset: All single-byte codepage; All double byte codepage.
- Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII

**Power Supply**

100, 115, 200 and 230 V AC  $\pm$  10%; 50 Hz to 60 Hz

**Printer Operating Environment**

**Operating Temperature:**

4° to 40°C (40° to 104°F)

**Storage Temperature:**

0° to 70°C (32° to 120°F)

**Humidity:** 10 to 90% (non-condensing)

**Bar Code Symbologies**

Code 2 of 5, Code 11, Code 39, Code 93, Code 128, Codabar, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-ITF

**2D:** Code One, Code 16K, Code 49, DataMatrix, MaxiCode, PDF417, QR Code

**Standards Supported**

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; ISBT 128

**Regulatory Approvals**

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

**Options**

Auto-peel; Bitmap and outline Kanji/Katakana; RF Gateway (2.4 GHz); Cutter/tray; Memory expansion to 512K NVRAM; Storage expansion to 8 MB Flash

**North America**

Corporate Headquarters  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2<sup>nd</sup> Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Europe/  
Middle East & Africa**

Headquarters  
Sovereign House  
Vastern Road  
Reading, Berkshire RG1 8BT  
United Kingdom  
tel: +44.118.987.9400  
fax: +44.118.987.9401

**Gothenburg**

Idrottsvägen 10  
P.O. Box 123  
SE-431 22 Mölndal  
Sweden  
tel: +46.31.869500  
fax: +46.31.869595

**Asia/  
Latin America**

Hong Kong  
26-12 Shell Tower  
Times Square  
1 Matheson Street  
Causeway Bay  
Hong Kong  
tel: 852.2574.9777  
fax: 852.2574.9725

**Singapore**

25-16 International Plaza  
10 Anson Road, 079903  
tel: 65.324.8391  
fax: 65.324.8393

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest NSW 2065  
Australia  
tel: 61.2.9901.2065  
fax: 61.2.9954.6300

**South America and Mexico**

2572 White Road  
Irvine, California 92614  
tel: 949.975.1905  
fax: 949.975.1913

**Worldwide**

**Fax Document Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2001 IntermeC Technologies Corporation. All rights reserved. IntermeC is a registered trademark of IntermeC Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608566-01D 08/01

In a continuing effort to improve our products, IntermeC Technologies Corporation reserves the right to change specifications and features without prior notice.

