

Intermec

Product Profile



- Rugged housing built for the field environment
- Weather resistant and highly functional
- Workboard style has holder for the 700 Series Mobile Computer
- 4" (10.2 cm) paper width capability
- 40-column format, with optional compressed 80-column capability
- Magstripe card reader option

P W 4 0 F O U R (4) I N C H W O R K B O A R D P R I N T E R

The Intermec PW40 thermal workboard printer is the newest addition to the Intermec line of workboard printers, designed specifically to hold the new Intermec 700 Series Mobile Computer. With a design that is both durable and weather resistant, the PW40 can take the punishment of daily work environments and is easily incorporated into the field. In addition, its functional design makes paper loading simple because roll-type paper fits easily into place.

The rugged one-piece solution allows the user the convenience of a joined device, with a hand strap. Additionally, the user can charge both the printer and mobile computer with one charge source.

The reliable four inch thermal printer mechanism on the PW40 offers exceptional print clarity with the versatility of printing text, graphics and logos. It can quickly print standard 40-column receipts, yet provides users with a 4-inch paper width capability to accommodate compressed 80-column

formats. With the flexibility to provide a compressed 80-column receipt, the field worker is relieved of having to carry the bulk of a larger 80-column printer. The PW40 easily handles 120 feet of thermal paper, reducing the frequency of changing paper rolls.

A vehicle charger option ensures a long day's work in the field. With a patented sleep mode for battery conservation, the PW40 automatically activates itself when it senses data input.

With the Bluetooth equipped PW40, mobile workers have the ability to begin printing while the 700 is away from the workboard. No longer needing to go back to a truck to or walk down an aisle to begin printing a ticket saves the driver valuable time. They can begin printing from up to 30 feet (10m) away.

The Intermec PW40 is fully compatible with the Intermec 6808, 681, 682 and 782 line of printers and is backed by a one-year warranty.

Intermec

Physical Description

The Intermec PW40 thermal workboard printer is a reliable four inch printer that offers exceptional print clarity along with the versatile capability of printing text, graphics and logos.

Physical Characteristics

Without Card Reader

Length: 21cm (8.25")

Height: 6.7cm (2.62")

Width: 35.25cm (13.9")

Weight Empty: .95kg (2.11 lbs.)

With batteries: 1.13kg (2.51 lbs.)

With batteries and paper: 1.39kg (3.07 lbs.)

With Card Reader

Length: 21cm (8.25")

Height: 8.57cm (3.38")

Width: 35.25cm (13.9")

Weight Empty: 1kg (2.21 lbs.)

With batteries: 1.18kg (2.62 lbs.)

With batteries and paper: 1.43kg (3.16 lbs.)

Bluetooth™

Length: 21cm (8.25")

Height: 6.7cm (2.62")

Width: 35.25cm (13.9")

Weight Empty: 95kg (2.11 lbs.)

With batteries: 1.13kg (2.11 lbs.)

With batteries and paper: 1.39kg (3.07 lbs.)

Standard Features

Direct thermal line printer able to print characters, graphics and bar codes.

Power

Supply: Two internal batteries; user replaceable

Battery Type: Lithium Ion 1.8 amp/hr, 7.2v, 2200mAh each

Battery Life: Print duration per charge is over 9144cm (3600")

AC Adapter/Recharging: Three hours to quick charge or nine hours to full charge, using a 12V vehicle charger with adapter or standard AC wall charger with power adapter.

Hardware

Interfaces: RS-232 serial

Print Specifications

Print Resolution: 203 dots per inch (dpi)

Print Width: 11.2cm (4.4")

Print Speed: 5.1cm (2") per second

Characters/Fonts

Three resident fonts and at least four additional standard downloaded fonts supplied. Other fonts can be purchased.

Warranty

One year warranty. Additional service packages available.

Environment

Operating Temperature: -20° to 50° C (-4° to 122° F)

Operating Temperature with Card Reader: -10° to 50° C (14° to 122° F)

Drop Survival: Withstands multiple 122cm (4') drops to concrete

Regulatory Approvals

FCC Title 47, Part 15, Subpart B, Class B; EN 55022 Class B; EN 50082-1

Restrictions on Use

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.



North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/ Middle East & Africa Headquarters

Reading International Business Park
Basingstoke Road
Reading RG2 6DD
United Kingdom
tel: 44.118.923.0800
fax: 44.118.923.0801

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86.10.5165.5922
Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
St. Leonards, NSW 2065
Australia
tel: 61.2.9330.4400
fax: 61.2.9437.0204

**South America & Mexico
Intermec South America Ltda.**
Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico
Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

OEM Sales

tel: 425.348.2762

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
611286-01D 12/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

