

**Intermec**

## Product Profile

- Field proven industrial strength
- Rugged metal frame and enclosure
- 6" print width
- Internal Ethernet network interface card optional
- Free LabelShop™ label design / print software
- InterDriver™ Windows printer driver included



### EasyCoder® 3600 PRINTER

Intermec's EasyCoder 3600 is a versatile industrial strength printer based on the legendary 3400, intended for users that require 6" wide labels or tags. The EasyCoder 3600 is ideal for wide-format compliance shipping and container labels, such as ODETTE. Printing large text for applications requiring maximum readability such as chemical drum or pallet labeling is easy using the large outline font included on the 3600.

The 3600 printer features label self-strip as standard. The self-strip feature peels the label away from the liner and presents the label to the operator for easier and faster demand labeling.

A serial communications interface is standard on the 3600, with Centronics Parallel, IBM Coax™, Twinax™, and internal EasyLAN™ 10i network interface connections as optional. The internal Ethernet adapter provides high throughput and network management without the complexity, space requirements and fragility of external print servers.

Intermec's LabelShop™ START design and print software and InterDriver™ Windows printer drivers are included, free of charge, with every printer.

Industrial-strength design and long lasting performance – it all adds up to the solid reputation that organizations worldwide have come to trust from the industry's leading manufacturer.

Intermec

**Applications**

Direct Thermal and Thermal Transfer Printer for high volume wide self-adhesive label, ticket and tag applications. Internal rewind and self-strip.

**Model**

EasyCoder 3600

**Physical Characteristics**

**Length:** 44 cm (17.25")

**Height:** 27.7 cm (10.9")

**Width:** 30.5 cm (12")

**Weight:** 20.4 kg (45 lbs.)

**Print Specifications**

**Element:** 0.125 mm (0.00492")

**Maximum Length:** Unlimited

**Maximum Width:** 168 mm (6.6")

**"X" Dimension:** 0.13 to 1.27 mm (5 to 50 mil)

**Speed:** 51, 77, 102 or 127 mm/sec (Select 2", 3", 4" or 5" sec)

**Resolution:** 8 dots/mm (203 dpi)

**Media Specifications**

**Roll:** 152 m (6000" linear)

**Roll Dimensions:** 213mm (8.38")

**Width:** 76 to 170 mm (3 to 6.7")

**Thickness:** .08 to .3 mm (0.003 to 0.012")

**Core size:** 76 mm (3")

**Ribbon Specifications-**

**Roll:** 152m (6000" linear)

**Widths:** 77, 104, 137, & 170 mm (3", 4.1", 5.4", & 6.7")

**Standard Features**

- Self-strip with full roll liner takeup
- Digital thermal compensation – dot-by-dot – electronics for excellent print quality, even for rotated bar codes
- Industrial design with enclosed label supply
- 128K NVRAM for permanent storage of downloaded fonts, graphics, and label formats

**Fonts and Graphics**

- 21 resident bit-mapped fonts (includes OCR-A and OCR-B)
- Outline font
- Supports user-defined fonts and graphics

**Language**

- IPL2™ (Intermec Printer Language 2)
- Backward Compatibility with 86XX

**Connectivity**

- Serial interface standard
- Centronics Parallel interface optional
- Internal Ethernet interface optional
- Internal IBM Twinax or Coax interface optional

**Serial Communications**

**Rate:** 1,200 to 19,200 bps

**Flow Control:** XON/XOFF, ready/busy

**Asynchronous:** RS-232-C, RS-422, RS-485

**Software**

- LabelShop™ START label design and print software
- Intermec InterDriver™ standard, Windows 3.x, 9x, NT 4.0/5.0, Windows 2000
- Intermec ActiveX® controls standard, Windows 9x, NT 4.0/5.0, Windows 2000
- PrintSet™ printer configuration utility, Windows 9x, NT 4.0/5.0, Windows 2000
- NetPilot™ + Thin Wizard™ network configuration utility (with optional Ethernet), Windows 9x, NT 4.0/5.0

**Character Sets**

Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII

**Power Supply**

100, 115, 200 and 230 V AC +10%; 50 Hz to 60 Hz

**Environment**

**Operating Temperature:** 4° to 40°C (41° to 104°F)

**Storage Temperature:** 0° to 70°C (32° to 120°F)

**Humidity:** Non-condensing (10 to 90%)

**Bar Code Symbolologies**

Code 2 of 5, Code 11, Code 39, Code 93, Code 128, Codabar, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-ITF

**2D:** Code One, Code 16K, Code 49, DataMatrix, MaxiCode, PDF417

**Standards Supported – Partial Listing**

AIAG Primary Metals; AIAB B-10; EIA (shipping container); LOGMARS; MITL; ODETTE; TCIF (shipping label); UCC/EAN 128 Serial Shipping Container; UPC/EAN Shipping Container

**Regulatory Approvals**

CSA certified (C22.2 No. 950-M89) 115V; ICES-003 Class B 115V; EC EN 55022 (CISPR22) Class B; 100V, 200V, 230V; FCC Part 15, Class B 115V; FTZ VFG 243/1992; TÜV GS licensed; (IEC 950 & EN 60950) 230V; UL® listed (1950) 100V, 115V, 200V; Compliant with all relevant EU directives.

**Options**

Memory expansion to 512K NVRAM; Bitmap and outline Kanji/Katakana

**North America**

Corporate Headquarters  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2<sup>nd</sup> Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Europe/  
Middle East & Africa**

Headquarters  
Sovereign House  
Vastern Road  
Reading, Berkshire RG1 8BT  
United Kingdom  
tel: +44.118.987.9400  
fax: +44.118.987.9401

**Gothenburg**

Idrottsvägen 10  
P.O. Box 123  
SE-431 22 Mölndal  
Sweden  
tel: +46.31.869500  
fax: +46.31.869595

**Asia/  
Latin America**

Hong Kong  
26-12 Shell Tower  
Times Square  
1 Matheson Street  
Causeway Bay  
Hong Kong  
tel: 852.2574.9777  
fax: 852.2574.9725

**Singapore**

25-16 International Plaza  
10 Anson Road, 079903  
tel: 65.324.8391  
fax: 65.324.8393

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest NSW 2065  
Australia  
tel: 61.2.9901.2065  
fax: 61.2.9954.6300

**South America and Mexico**

17921 B Skypark Circle  
Irvine, California 92614  
tel: 949.442.9393  
fax: 949.757.1687

**Worldwide**

**Fax Document Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608567-01D 11/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.